

S7L - 25W Series

25W 2:1 Regulated Single & Dual output

SCHMID-M

Features

- Wide 2:1 Input Range
- Full SMD Technology
- 1500 VDC Isolation
- Continuous Short Circuit Protection
- Efficiency up to 88%
- -40 ~ 85°C Operation Temperature Range



The S7L series is a family of cost effective 25W single & dual output DC-DC converters. These converters are made with nickle-coated brass case in a 2"x2" with high performance features such as 1500 VDC input/output isolation voltage, continuous short circuit protection with automatic restart and tight line / load regulation. Devices are encapsulated by using flame retardant resin. Input voltages of 12, 24 and 48 with output voltage of 3.3, 5, 7.2, 9, 12, 15, 18, 24, ± 3.3 , ± 5 , ± 7.2 , ± 9 , ± 12 , ± 15 , ± 18 , ± 24 Vdc. High performance features include high efficiency operation up to 88% and output voltage accuracy of $\pm 1\%$ maximum.

All specifications typical at Ta=25°C, nominal input voltage and full load unless otherwise specified

OUTPUT SPECIFICATIONS	
Voltage accuracy	$\pm 1\%$
Line regulation	$\pm 0.5\%$
Load regulation	Single (0% to 100% Load) $\pm 0.5\%$ Dual (10% to 100% Load) $\pm 0.5\%$
Ripple & noise(20 MHz bandwidth)(1)	100mV pk-pk
Over-current protection	140% of max. Iout
Short circuit protection	Indefinite(Automatic Recovery)
Temperature coefficient	$\pm 0.02\%/^{\circ}\text{C}$
Capacitor load(2)	See table

INPUT SPECIFICATIONS	
Voltage Range	See table
Start up Time(Nominal Vin and constant resistive load)	20mS, typ.
Max. Input Current	See table
No-Load Input Current	See table
Input Filter	Capacitors
Input Reflected Ripple Current(3)	35mA pk-pk

GENERAL SPECIFICATIONS	
Efficiency	See table
I/O Isolation Voltage(3 sec)	
Input/Output	1500Vdc
Case/Input & Output	1000Vdc
I/O Isolation Capacitance	1000 pF typ.
I/O Isolation Resistance	1000M Ohm
Switching Frequency	Typical 125kHz
Humidity	95% rel H
Reliability Calculated MTBF(MIL-HDBK-217 F)	>1.121 Mhrs
Safety Standard : (designed to meet)	IEC 60950-1



PHYSICAL SPECIFICATIONS	
Case Material	Nickel-coated Brass
Pin Material	$\varnothing 1.0\text{mm}$ Brass Solder-coated
Potting Material	Epoxy (UL94V-0-rated)
Weight	60.0g
Dimensions	2.00"x2.00"x0.40"

ENVIRONMENT SPECIFICATIONS	
Operating Temperature	-40°C~85°C(See Derating Curve)
Temperature	-40°C~65°C(For 100% load)
Maximum Case Temperature	100°C
Storage Temperature	-40°C~125°C
Cooling	Nature Convection

ABSOLUTE MAXIMUM RATINGS(4)	
These are stress ratings. Exposure of devices to any of these conditions may adversely affect long-term reliability.	
Input Surge Voltage(100mS)	
12 Models	25 Vdc max.
24 Models	50 Vdc max.
48 Models	100 Vdc max.
Soldering Temperature	260°C
(1.5mm from case 10sec.max.)	

S7L - 25W 2:1 Regulated Single & Dual output

PARTNUMBER STRUCTURE



MODEL SELECTION GUIDE

MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current		EFFICIENCY @FL (%)	Capacitor Load (uF)
		No-Load (mA)	Full Load (mA)		Min. load (mA)	Full load (mA)		
S7-1205 S25L	9-18	20	2510	5	0	5000	83	3300
S7-127R2 S25L	9-18	20	2480	7.2	0	3472	84	2200
S7-1209 S25L	9-18	20	2480	9	0	2777	84	1000
S7-1212 S25L	9-18	20	2480	12	0	2083	84	1000
S7-1215 S25L	9-18	30	2450	15	0	1666	85	680
S7-1218 S25L	9-18	30	2450	18	0	1388	85	470
S7-1224 S25L	9-18	30	2450	24	0	1041	85	470
S7-123R3D25L	9-18	20	1718	±3.3	±0	±2500	80	±1500
S7-1205D25L	9-18	25	2540	±5	±0	±2500	82	±1500
S7-127R2D25L	9-18	25	2510	±7.2	±0	±1736	83	±1000
S7-1209D25L	9-18	25	2480	±9	±0	±1388	84	±680
S7-1212D25L	9-18	30	2480	±12	±0	±1041	84	±470
S7-1215D25L	9-18	30	2450	±15	±0	±833	85	±330
S7-1218D25L	9-18	35	2450	±18	±0	±694	85	±220
S7-1224D25L	9-18	35	2450	±24	±0	±520	85	±220
S7-243R3 S25L	18-36	25	838	3.3	0	5000	82	3300
S7-2405 S25L	18-36	25	1240	5	0	5000	84	3300
S7-247R2 S25L	18-36	25	1240	7.2	0	3472	84	2200
S7-2409 S25L	18-36	25	1240	9	0	2777	84	1000
S7-2412 S25L	18-36	25	1225	12	0	2083	85	1000
S7-2415 S25L	18-36	25	1225	15	0	1666	85	680
S7-2418 S25L	18-36	25	1225	18	0	1388	85	470
S7-2424 S25L	18-36	25	1211	24	0	1041	86	470
S7-243R3D25L	18-36	25	859	±3.3	±0	±2500	80	±1500
S7-2405D25L	18-36	25	1240	±5	±0	±2500	84	±1500
S7-247R2D25L	18-36	25	1240	±7.2	±0	±1736	84	±1000
S7-2409D25L	18-36	25	1240	±9	±0	±1388	84	±680
S7-2412D25L	18-36	25	1225	±12	±0	±1041	85	±470
S7-2415D25L	18-36	25	1211	±15	±0	±833	86	±330
S7-2418D25L	18-36	25	1211	±18	±0	±694	86	±220
S7-2424D25L	18-36	30	1197	±24	±0	±520	87	±220

S7L - 25W 2:1 Regulated Single & Dual output

MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current		EFFICIENCY @FL (%)	Capacitor Load (uF)
		No-Load (mA)	Full Load (mA)		Min. load (mA)	Full load (mA)		
S7-483R3 S25L	36-72	20	429	3.3	0	5000	80	3300
S7-4805 S25L	36-72	20	627	5	0	5000	83	3300
S7-487R2 S25L	36-72	20	620	7.2	0	3472	84	2200
S7-4809 S25L	36-72	20	620	9	0	2777	84	1000
S7-4812 S25L	36-72	20	612	12	0	2083	85	1000
S7-4815 S25L	36-72	20	605	15	0	1666	86	680
S7-4818 S25L	36-72	20	605	18	0	1388	86	470
S7-4824 S25L	36-72	25	592	24	0	1041	88	470
S7-483R3D25L	36-72	20	429	±3.3	±0	±2500	80	±1500
S7-4805D25L	36-72	20	620	±5	±0	±2500	84	±1500
S7-487R2D25L	36-72	20	620	±7.2	±0	±1736	84	±1000
S7-4809D25L	36-72	20	620	±9	±0	±1388	84	±680
S7-4812D25L	36-72	20	612	±12	±0	±1041	85	±470
S7-4815D25L	36-72	20	598	±15	±0	±833	87	±330
S7-4818D25L	36-72	20	598	±18	±0	±694	87	±220
S7-4824D25L	36-72	25	598	±24	±0	±520	87	±220


NOTE

1. Ripple/Noise measured with 20MHz bandwidth and 1.0uF ceramic capacitor.
2. Tested by minimal V_{in} and constant resistive load.
3. Measured Input reflected ripple current with a simulated source inductance of 12uH.
4. Exceeding the absolute ratings of the unit could cause damage. It is not allowed for continuous operating.
5. Operation under no-load conditions will not damage these devices, however they may not meet all listed specifications.

TEST CONFIGURATIONS

Input Reflected Ripple Current Test Step


Input reflected ripple current is measured through a source inductor L_{in} (12uH) and a source capacitor C_{in} (47uF, ESR < 1.0Ω at 100KHz) at nominal input and full load.




Output Ripple & Noise Measurement Test

To reduce ripple and noise, it is recommended to use a 1uF ceramic disk capacitor and a 10uF electrolytic capacitor to at the output.

Single Output




Dual Output




S7L - 25W 2:1 Regulated Single & Dual output


ELECTRICAL CHARACTERISTIC CURVES



12 Models




24 Models



48 Models

MECHANICAL SPECIFICATIONS



PIN CONNECTIONS

PIN NUMBER	SINGLE	DUAL
1	+V Input	+V Input
2	-V Input	-V Input
3	+V Output	+V Output
4	N.P.	Common
5	-V Output	-V Output

All dimensions are typical in millimeters (inches).

1. Pin diameter: 1.0 ± 0.05 (0.04 ± 0.002)
2. Pin pitch and length tolerance: ± 0.35 (± 0.014)
3. Case Tolerance: ± 0.5 (± 0.02)